SAFETY DATA SHEET



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

MAP-Pro™ Premium Hand Torch Fuel Name of the substance

601-011-00-9 (Index number) Identification number

Registration number

Synonyms None. SDS number WC001

MAP-Pro™, PRO-Max™ **Product code** Issue date 25-November-2015

Version number

10-March-2021 **Revision date** 10-March-2021 Supersedes date

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Hand Torch Fuel Uses advised against None known 1.3. Details of the supplier of the safety data sheet

Manufacturer/Supplier Worthington Cylinders GmbH **Address** Beim Flaschenwerk 1, A-3291

Kienberg bei Gaming

Austria

E-mail SDSRequest@worthingtonindustries.com

Telephone 1-800-359-9678

1-703-527-3887 International / CHEMTREC 1-800-424-9300 US **Emergency telephone**

(CCN 24850)

1.4. Emergency telephone number

112 (Available 24 hours a day. SDS/Product information may not be available for General in EU

the Emergency Service.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The substance has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Flammable gases Category 1A H220 - Extremely flammable gas. Gases under pressure Liquefied gas H280 - Contains gas under pressure; may explode if heated.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Hazard pictograms



Signal word Danger

Hazard statements

Contains gas under pressure; may explode if heated. H280

Extremely flammable gas. H220

Precautionary statements

Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P210

MAP-Pro™ Premium Hand Torch Fuel 909050 Version #: 03 Revision date: 10-March-2021 Issue date: 25-November-2015 1/8 Response

P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381 In case of leakage, eliminate all ignition sources.

Storage

P410 + P403 Protect from sunlight. Store in a well-ventilated place.

Disposal Not assigned.

Supplemental information on

the label

None.

2.3. Other hazards

May displace oxygen and cause rapid suffocation. Contact with liquefied gas may cause frostbite. This substance does not meet vPvB / PBT criteria of Regulation (EC) No 1907/2006, Annex XIII. The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.1. Substances

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Propylene	99.5 - 100	115-07-1 204-062-1	-	601-011-00-9	
Classification: Flam. Gas 1A;H220, Press. Gas;H280					

Impurities

parities					
Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Propane	0 - 0.5	74-98-6 200-827-9	-	601-003-00-5	

List of abbreviations and symbols that may be used above

Note U (Table 3.1): When put on the market gases have to be classified as "Gases under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

Composition comments

The full text for all H-statements is displayed in section 16.

Gas concentrations are in percent by volume.

SECTION 4: First aid measures

General information

First aid personnel must be aware of own risk during rescue. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

4.1. Description of first aid measures

Inhalation

Remove from further exposure. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. If respiratory tract irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to-mouth resuscitation.

Skin contact

Not likely, due to the form of the product. If frostbite occurs, immerse affected area in warm water (not exceeding 105°F/41°C). Keep immersed for 20 to 40 minutes. Get medical attention immediately.

Eye contact

Not likely, due to the form of the product. If frostbite occurs, immediately flush eyes with plenty of warm water (not exceeding 105°F/41°C) for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention promptly if symptoms persist or occur after washing.

Ingestion

This material is a gas under normal atmospheric conditions and ingestion is unlikely.

4.2. Most important symptoms and effects, both acute and

delayed

Exposure to rapidly expanding gas or vapourizing liquid may cause frostbite ("cold burn"). Very high exposure can cause suffocation from lack of oxygen. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Asphyxiation may bring about unconsciousness without warning and so rapidly that victim may be unable to protect themself.

4.3. Indication of any immediate medical attention and special treatment needed Exposure may aggravate pre-existing respiratory disorders. Provide general supportive measures and treat symptomatically.

SECTION 5: Firefighting measures

General fire hazards Extremely flammable gas. Contents under pressure. Pressurised container may explode when

exposed to heat or flame.

5.1. Extinguishing media

Suitable extinguishing media

Dry chemical powder. Carbon dioxide (CO2). Water fog. Foam.

909050 Version #: 03 Revision date: 10-March-2021 Issue date: 25-November-2015

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Extremely flammable gas. May form explosive mixtures with air. Gas may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters Special protective equipment for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire fighting procedures

Do not extinguish fires unless gas flow can be stopped safely; explosive re-ignition may occur. Promptly isolate the scene by removing all persons from the vicinity of the incident. No action shall be taken involving any personal risk or without suitable training. For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus. Stop flow of material. Use water to keep fire exposed containers cool and to protect personnel effecting shutoff. If a leak or spill has not ignited, use water spray to disperse the vapors and to protect personnel attempting to stop leak. Prevent runoff from fire control or dilution from entering streams, sewers or drinking water supply.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Cool containers exposed to flames with water until well after the fire is out.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Evacuate the area promptly. Keep unnecessary personnel away. Wear appropriate personal protective equipment.

For emergency responders

No action shall be taken involving any personal risk or without suitable training. In the event of a leak evacuate all personnel until ventilation can restore oxygen concentrations to safe levels. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Wear appropriate protective equipment and clothing during clean-up.

6.2. Environmental precautions

Should not be released into the environment. Prevent further leakage or spillage if safe to do so.

6.3. Methods and material for containment and cleaning up Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Stop leak if you can do so without risk. If possible, turn leaking containers so that gas escapes rather than liquid. Isolate area until gas has dispersed.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Do not smoke. All equipment used when handling the product must be grounded. Do not breathe gas. Avoid prolonged exposure. Do not enter storage areas or confined spaces unless adequately ventilated. Use only outdoors or in a well-ventilated area. Oxygen concentration should not fall below 19.5 % at sea level (pO2 = 135 mmHg). Mechanical ventilation or local exhaust ventilation may be required. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Do not store, incinerate, or heat this material above 120 degrees Fahrenheit. Keep away from heat, sparks and open flame. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Protect cylinders from damage. Stored containers should be periodically checked for general condition and leakage. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

Hand Torch Fuel 7.3. Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No exposure limits noted for ingredient(s). Occupational exposure limits

Biological limit values No biological exposure limits noted for the ingredient(s).

Recommended monitoring

procedures

Derived no effect levels

(DNELs)

Not available.

Not available.

Predicted no effect concentrations (PNECs)

Exposure guidelines

Follow standard monitoring procedures.

Follow standard monitoring procedures.

MAP-Pro™ Premium Hand Torch Fuel

SDS UK 909050 Version #: 03 Revision date: 10-March-2021 Issue date: 25-November-2015

8.2. Exposure controls

Appropriate engineering

controls

Provide adequate ventilation and minimize the risk of inhalation of gas. Use process enclosures,

local exhaust ventilation, or other engineering controls to control airborne levels below

recommended exposure limits.

Individual protection measures, such as personal protective equipment

General information Use personal protective equipment as required. Personal protection equipment should be chosen

according to the CEN standards and in discussion with the supplier of the personal protective

equipment.

Wear approved safety glasses or goggles. Face shield is recommended. Eye protection should Eye/face protection

meet standard EN 166.

Skin protection

- Hand protection Wear suitable gloves tested to EN374. Wear cold insulating gloves.

- Other Wear protective clothing appropriate for the risk of exposure.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

WARNING! Air-purifying respirators do not protect workers in oxygen deficient atmospheres. Contact with liquefied gas might cause frostbites, in some cases with tissue damage. Wear

appropriate thermal protective clothing, when necessary.

Do not eat, drink or smoke when using the product. Wash thoroughly after handling. Provide Hygiene measures

eyewash station and safety shower. Handle in accordance with good industrial hygiene and safety

practices.

Environmental exposure

Thermal hazards

controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or

engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Gas. **Physical state**

Form Compressed liquefied gas.

Colourless. Colour

Odour Hydrocarbon or mercaptan if odorized.

Odour threshold Not determined. -185 °C (-301 °F) Melting point/freezing point **Boiling point or initial boiling** -48 °C (-54.4 °F)

point and boiling range

Boiling point pressure 101.33 kPa

Extremely flammable gas. **Flammability**

Lower and upper explosion limit

Explosive limit - lower (%) 2 % v/v Explosive limit - upper 11 % v/v

(%)

Flash point -107.8 °C (-162.0 °F) 497.22 °C (927 °F) **Auto-ignition temperature Decomposition temperature** Not determined.

Not applicable. pН Kinematic viscosity Not determined.

Solubility

Solubility (water) 384 mg/l - Slightly soluble in water.

Partition coefficient 1.77

n-octanol/water (log value)

109.73 PSIG Vapour pressure 21 °C (69.8 °F) Vapour pressure temp.

Density and/or relative density

0.52 (liquid) (Water=1) (20 °C (68 °F)) Relative density

Vapour density 1.5 (gas) (Air=1) (0 °C (32 °F))

Particle characteristics

Particle size Not applicable.

MAP-Pro™ Premium Hand Torch Fuel

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No relevant additional information available.

9.2.2. Other safety characteristics

Not determined. **Evaporation rate**

Molecular formula C3-H6 Molecular weight 42 g/mol Percent volatile 100 %

16.7 mN/m (90 °C (194 °F)) Surface tension

SECTION 10: Stability and reactivity

Reacts violently with strong oxidants, nitrites, inorganic chlorides, chlorites and perchlorates 10.1. Reactivity

causing fire and explosion hazard.

Stable under normal temperature conditions and recommended use. 10.2. Chemical stability

10.3. Possibility of hazardous

reactions

Polymerization will not occur. May form explosive mixture with air. This product may react with

oxidizing agents.

10.4. Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Strong oxidising agents. Strong acids. Halogens. Nitrates. 10.5. Incompatible materials

10.6. Hazardous Thermal decomposition of this product can generate carbon monoxide and carbon dioxide.

decomposition products Hydrocarbons.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

High concentrations: Suffocation (asphyxiant) hazard - if allowed to accumulate to concentrations Inhalation

> that reduce oxygen below safe breathing levels. Breathing of high concentrations may cause dizziness, light-headedness, headache, nausea and loss of co-ordination. Continued inhalation

may result in unconsciousness.

Skin contact Contact with liquefied gas may cause frostbite. Contact with liquefied gas may cause frostbite. Eye contact

Ingestion This material is a gas under normal atmospheric conditions and ingestion is unlikely.

Exposure to rapidly expanding gas or vapourizing liquid may cause frostbite ("cold burn"). Very **Symptoms**

high exposure can cause suffocation from lack of oxygen. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Asphyxiation may bring about unconsciousness without warning and so rapidly that victim may be unable to protect themself.

11.1. Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Toxicological data

Impurities Test Results Species

Propane (CAS 74-98-6)

Acute Inhalation Gas

LC50 Rat > 80000 ppm, 15 Minutes

Skin corrosion/irritation Serious eye damage/eye

irritation

Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

Respiratory sensitisation Skin sensitisation Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Germ cell mutagenicity Carcinogenicity Based on available data, the classification criteria are not met.

IARC Monographs. Overall Evaluation of Carcinogenicity

Propylene (CAS 115-07-1) 3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicity Based on available data, the classification criteria are not met. Specific target organ toxicity -Based on available data, the classification criteria are not met.

single exposure

MAP-Pro™ Premium Hand Torch Fuel

909050 Version #: 03 Revision date: 10-March-2021 Issue date: 25-November-2015 Specific target organ toxicity -

repeated exposure

Based on available data, the classification criteria are not met.

Not relevant, due to the form of the product. **Aspiration hazard**

Mixture versus substance

information

No information available.

11.2. Information on other hazards

Endocrine disrupting properties

The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU)

2018/605 at levels of 0.1% or higher.

Exposure over a long period of time may cause central nervous system effects. Other information

SECTION 12: Ecological information

The product is not expected to be hazardous to the environment. 12.1. Toxicity

12.2. Persistence and

degradability

Not relevant, due to the form of the product.

Not relevant, due to the form of the product. 12.3. Bioaccumulative potential

Partition coefficient n-octanol/water (log Kow)

Propylene (CAS 115-07-1) 1.77

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil Not relevant, due to the form of the product.

12.5. Results of PBT and vPvB

12.6. Endocrine disrupting

assessment

properties

This substance does not meet vPvB / PBT criteria of Regulation (EC) No 1907/2006, Annex XIII.

The product does not contain components considered to have endocrine disrupting properties

according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7. Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

Substance Global Warming Potential per (Annex IV), Regulation 517/2014/EU on fluorinated greenhouse gases, as amended

Propane (CAS 74-98-6) 3 Propylene (CAS 115-07-1) 2

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose in accordance with all applicable regulations.

Empty containers should be taken to an approved waste handling site for recycling or disposal. Contaminated packaging

EU waste code 16 05 04*

The waste code should be assigned in discussion between the user, the producer and the waste disposal company. The Waste code should be assigned in discussion between the user, the

producer and the waste disposal company.

Use the container until empty. Do not dispose of any non-empty container. Empty containers have Disposal methods/information

residual vapor that is flammable and explosive. Cylinders should be emptied and returned to a hazardous waste collection point. Do not puncture or incinerate even when empty. Dispose in

accordance with all applicable regulations.

Dispose of in accordance with local regulations. Special precautions

SECTION 14: Transport information

ADR

UN1077 14.1. UN number

PROPYLENE 14.2. UN proper shipping

name

14.3. Transport hazard class(es)

Class 2.1 Subsidiary risk 2.1 Label(s) Hazard No. (ADR) 23 **Tunnel restriction code** B/D 14.4. Packing group 14.5. Environmental hazards No

14.6. Special precautions

MAP-Pro™ Premium Hand Torch Fuel

Read safety instructions, SDS and emergency procedures before handling.

for user

909050 Version #: 03 Revision date: 10-March-2021 Issue date: 25-November-2015

```
RID
```

UN1077 14.1. UN number 14.2. UN proper shipping **PROPYLENE** 14.3. Transport hazard class(es) Class 2 1 Subsidiary risk 2.1 (+13) Label(s) 14.4. Packing group 14.5. Environmental hazards No 14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling. for user **ADN** UN1077 14.1. UN number 14.2. UN proper shipping **PROPYLENE** name 14.3. Transport hazard class(es) 2.1 Class Subsidiary risk 2.1 Label(s) 14.4. Packing group 14.5. Environmental hazards No Read safety instructions, SDS and emergency procedures before handling. 14.6. Special precautions for user 14.1. UN number UN1077 14.2. UN proper shipping Propylene name 14.3. Transport hazard class(es)

IATA

Class 2.1

Subsidiary risk 2.1 Label(s) 14.4. Packing group 14.5. Environmental hazards No **ERG Code**

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

IMDG

14.1. UN number UN1077 **PROPYLENE** 14.2. UN proper shipping

name

14.3. Transport hazard class(es) Class 2.1

Subsidiary risk 14.4. Packing group 14.5. Environmental hazards Marine pollutant No

F-D, S-U **EmS** Read safety instructions, SDS and emergency procedures before handling. 14.6. Special precautions

for user

14.7. Maritime transport in bulk Not applicable.

according to IMO instruments

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorisation, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended Propylene (CAS 115-07-1)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Propane (CAS 74-98-6) Propylene (CAS 115-07-1)

Other regulations The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP

Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation

(EC) No 1907/2006, as amended.

National regulations Young people under 18 years old are not allowed to work with this product according to EU

Directive 94/33/EC on the protection of young people at work, as amended.

Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as

amended.

15.2. Chemical safety

assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.

ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road.

IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous

Chemicals in Bulk.

IMDG Code: International Maritime Dangerous Goods Code.

LC50: Lethal Concentration, 50%.

MARPOL: International Convention for the Prevention of Pollution from Ships. RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short-Term Exposure Limit. TWA: Time Weighted Average Value.

References ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

EPA: AQUIRE database

HSDB® - Hazardous Substances Data Bank

IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens

NLM: Hazardous Substances Data Base

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation

methods and test data, if available.

Full text of any H-statements not written out in full under

H280 Contains gas under pressure; may explode if heated.

Sections 2 to 15
Training information

Follow training instructions when handling this material.

Disclaimer

All information in this Safety Data Sheet is believed to be accurate and reliable. However, no guarantee or warranty of any kind is made with regard to the accuracy of information or the suitability of the recommendations contained herein. It is the user's responsibility to assess the safety and toxicity of this product under their own conditions of use and to comply with all applicable laws and regulations.