

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture
Trade name : Fix-a-Flat
Product code : S60420, S60430, S60369, S60410
Vaporizer : Aerosol

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Adhesives, sealants
Restrictions on use : No additional information available

1.4. Supplier's details

Supplier

ITW Global Tire Repair, Inc.
125 Venture Drive, Suite 210, San Luis Obispo, CA 93401, USA
Tel: (888) 457-5463 (Toll Free)

1.5. Emergency phone number

Emergency number : Chemtel: +1(813)248-0585 (International)

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR § 1910.1200)

Aerosol, Category 3	H229	Pressurized container; may burst if heated.
Skin sensitization, Category 1	H317	May cause an allergic skin reaction.
Full text of H statements : see section 16		

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Warning
Hazard statements (GHS US) : H229 - Pressurized container; may burst if heated
H317 - May cause an allergic skin reaction
Precautionary statements (GHS US) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251 - Do not pierce or burn, even after use.
P261 - Avoid breathing spray.
P272 - Contaminated work clothing must not be allowed out of the workplace.
P280 - Wear protective gloves.
P302+P352 - If on skin: Wash with plenty of soap and water.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P333+P313 - If skin irritation or rash occurs: Get medical advice or attention.

Fix-a-Flat

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

P362+P364 - Take off contaminated clothing and wash it before reuse.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C).
P501 - Dispose of contents and container to a hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Comments : The exact percentage (concentration) in the composition has been withheld as a trade secret in accordance with paragraph (i) of § 1910.1200

Name	Product identifier	%	GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR § 1910.1200)
Glycerol	CAS-No.: 56-81-5	1 - 5	Not classified
Quartz (SiO ₂)	CAS-No.: 14808-60-7	0.1 - 1	Carc. 1A, H350 STOT RE 1, H372
Magnesium oxide	CAS-No.: 1309-48-4	0.1 - 1	Not classified
Cellulose	CAS-No.: 9004-34-6	0.1 - 1	Not classified
Propan-2-ol	CAS-No.: 67-63-0	0.01 – 0.1	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
2-methylisothiazol-3(2H)-one	CAS-No.: 2682-20-4	0.0015 - 0.01	Acute Tox. 2 (Inhalation), H330 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Oral), H301 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Comments : SCL for Skin Sens. 1A: ≥ 0.0015 %
Full text of hazard classes and H-statements : see section 16

Fix-a-Flat

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: Call a poison center/doctor/physician if you feel unwell. Never give anything by mouth to an unconscious person.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	: Rinse mouth out with water. Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: May cause shortness of breath, tightness of the chest, a sore throat and cough.
Symptoms/effects after skin contact	: May cause an allergic skin reaction. Redness. Itching. Skin rash/inflammation.
Symptoms/effects after eye contact	: Direct contact with the eyes is likely to be irritating. Redness. Itching. Lacrimation. Blurred vision.
Symptoms/effects after ingestion	: Not expected to present a significant hazard under anticipated conditions of normal use.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Alcohol-resistant foam. Carbon dioxide. Dry powder. Water spray. Use extinguishing agent suitable for surrounding fire.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: Burning produces stinking and toxic fumes. In case of fire and/or explosion do not breathe fumes.
Explosion hazard	: Contains gas under pressure; may explode if heated.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon monoxide. Carbon dioxide.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Evacuate the danger area. Move containers from fire area if it can be done without personal risk. Exercise caution when fighting any chemical fire. Fight fire with normal precautions from a reasonable distance. Use water spray or fog for cooling exposed containers. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: May displace oxygen and cause rapid suffocation.
------------------	--

For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
----------------------	---

Fix-a-Flat

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Emergency procedures : Evacuate unnecessary personnel. Ventilate spillage area. Avoid breathing spray. Do not get in eyes, on skin, or on clothing. No action shall be taken without appropriate training or involving any personal risk.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel.

Environmental precautions : Avoid release to the environment. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Notify authorities if product enters sewers or public waters.

6.2. Methods and materials for containment and cleaning up

For containment : Stop leak, if possible without risk. Do not touch or walk on the spilled product. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for cleaning up : Move containers from spill area. Leave the product to evaporate. Absorb remaining liquid with sand or inert absorbent and remove to safe place. Clean area with detergent and water after spill clean-up. Prevent entry to sewers and public waters. Keep in suitable, closed containers for disposal. Dispose of as hazardous waste.

Other information : Dispose of via an authorised person/ licensed waste disposal contractor or by other suitable waste treatment techniques.

For further information refer to section 13, For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Ensure good ventilation of the work station. Avoid breathing spray. Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Pressurized container: Do not pierce or burn, even after use. Avoid release to the environment. Empty containers retain product residue and can be hazardous.

Hygiene measures : Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool. Store away from other materials. Keep away from food, drink and animal feed. Store in accordance with local, regional, national or international regulation. Do not store in unlabelled containers.

Incompatible materials : Direct sunlight. Heat sources. Extremely high or low temperatures.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Glycerol (56-81-5)	
USA - OSHA - Occupational Exposure Limits	
Local name	Glycerin (mist)
OSHA PEL TWA	15 mg/m ³ (Total dust) 5 mg/m ³ (Respirable fraction)

Fix-a-Flat

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Glycerol (56-81-5)	
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Cellulose (9004-34-6)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Cellulose
ACGIH OEL TWA	10 mg/m ³
Remark (ACGIH)	TLV® Basis: URT irr
Regulatory reference	ACGIH 2023
USA - OSHA - Occupational Exposure Limits	
Local name	Cellulose
OSHA PEL TWA	15 mg/m ³ (Total dust) 5 mg/m ³ (Respirable fraction)
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - Cal/OSHA - Occupational Exposure Limits	
Local name	Cellulose (paper fiber)
Cal/OSHA PEL (OEL TWA)	10 mg/m ³ (Total dust) 5 mg/m ³ (Respirable fraction)
Regulatory reference	California Division of Occupational Safety and Health (Cal/OSHA) - Permissible Exposure Limit for Chemical Contaminants (Table AC-1)
USA - NIOSH - Occupational Exposure Limits	
Local name	Cellulose
NIOSH REL 10h TWA	10 mg/m ³ (Total dust) 5 mg/m ³ (Respirable fraction)
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-1 (NIOSH Pocket Guide to Chemical Hazards (NPG))
Quartz (SiO₂) (14808-60-7)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Silica crystalline - quartz
ACGIH OEL TWA	0.025 mg/m ³ (R - Respirable particulate matter)
Remark (ACGIH)	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)
Regulatory reference	ACGIH 2022
USA - OSHA - Occupational Exposure Limits	
Local name	Quartz (Total Dust) (Silica: Crystalline)
Remark (OSHA)	Table Z-3. For OSHA PEL (TWA) use formula: (30 mg/m ³ / (%SiO ₂ +2)) for mg/m ³ . CAS No. source: eCFR Table Z-1.
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-3 Mineral Dusts
USA - Cal/OSHA - Occupational Exposure Limits	
Local name	Quartz
Cal/OSHA PEL (OEL TWA)	0.05 mg/m ³ (Silica, crystalline, respirable dust)
Regulatory reference	California Division of Occupational Safety and Health (Cal/OSHA) - Permissible Exposure Limit for Chemical Contaminants (Table AC-1)

Fix-a-Flat

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Quartz (SiO ₂) (14808-60-7)	
USA - NIOSH - Occupational Exposure Limits	
Local name	Quartz (Silica, crystalline, respirable dust)
NIOSH REL 10h TWA	0.05 mg/m ³
Remark (NIOSH)	Ca = Potential occupational carcinogens
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-1 (NIOSH Pocket Guide to Chemical Hazards (NPG))
Magnesium oxide (1309-48-4)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Magnesium oxide
ACGIH OEL TWA	10 mg/m ³ (I - Inhalable particulate matter)
Remark (ACGIH)	TLV® Basis: URT; metal fume fever. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2023
USA - OSHA - Occupational Exposure Limits	
Local name	Magnesium oxide fume - Total Particulate
OSHA PEL TWA	15 mg/m ³
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Propan-2-ol (67-63-0)	
USA - ACGIH - Occupational Exposure Limits	
Local name	2-Propanol
ACGIH OEL TWA	200 ppm
ACGIH OEL STEL	400 ppm
Remark (ACGIH)	TLV® Basis: Eye & URT irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2023
USA - ACGIH - Biological Exposure Indices	
Local name	2-PROPANOL
BEI (BLV)	40 mg/l Parameter: Acetone - Medium: urine - Sampling time: End of shift at end of workweek - Notations: B, Ns
Regulatory reference	ACGIH 2023
USA - OSHA - Occupational Exposure Limits	
Local name	Isopropyl alcohol
OSHA PEL TWA	980 mg/m ³ 400 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Monitoring methods	
Monitoring methods	Refer to all applicable national, international and local regulations or provisions.

Fix-a-Flat

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

8.2. Appropriate engineering controls

Appropriate engineering controls	: Handle in accordance with good industrial hygiene and safety procedures. Provide local exhaust or general room ventilation. Avoid all unnecessary exposure. Ensure exposure is below occupational exposure limits (where available).
Environmental exposure controls	: Avoid release to the environment. Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil.

8.3. Individual protection measures, such as personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment. Personal protective equipment should be chosen according to the NIOSH standards and in discussion with the supplier of the protective equipment.

Hand protection:
Chemical resistant gloves (according to NIOSH standard). Please follow the instructions related to the permeability and the penetration time provided by the manufacturer. Selection of protective gloves should be made based on the type of task performed.
Eye protection:
Use splash goggles when eye contact due to splashing is possible
Skin and body protection:
Wear suitable protective clothing. Skin protection appropriate to the conditions of use should be provided
Respiratory protection:
Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. All respirators must conform to specifications for efficiency and performance indicated by OSHA Standard 29 CFR 1910.134 and NIOSH Standards

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Gas
Appearance	: Aerosol.
Color	: According to product specification
Odor	: No data available
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Explosion limits	: No data available
Particle characteristics	: No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

Fix-a-Flat

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

SECTION 10 Stability and reactivity

10.1. Reactivity

Pressurized container: may burst if heated.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use. Hazardous polymerization: Will not occur.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7). Direct sunlight. High temperature. Heat or source of heat.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Glycerol (56-81-5)

LD50 oral rat	12600 mg/kg
---------------	-------------

Quartz (SiO₂) (14808-60-7)

LD50 oral rat	> 5000 mg/kg
---------------	--------------

LD50 dermal rat	> 5000 mg/kg
-----------------	--------------

Propan-2-ol (67-63-0)

LD50 oral rat	4570 mg/kg
---------------	------------

LD50 dermal rabbit	13400 mg/kg
--------------------	-------------

LC50 Inhalation - Rat	30 mg/l/4h
-----------------------	------------

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Quartz (SiO₂) (14808-60-7)

IARC group	1 - Carcinogenic to humans
------------	----------------------------

National Toxicity Program (NTP) Status	Known Human Carcinogens
--	-------------------------

Propan-2-ol (67-63-0)

IARC group	3 - Not classifiable
------------	----------------------

Fix-a-Flat

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not applicable

Fix-a-Flat	
Vaporizer	Aerosol
Viscosity, kinematic	No data available

Symptoms/effects after inhalation	: May cause shortness of breath, tightness of the chest, a sore throat and cough.
Symptoms/effects after skin contact	: May cause an allergic skin reaction. Redness. Itching. Skin rash/inflammation.
Symptoms/effects after eye contact	: Direct contact with the eyes is likely to be irritating. Redness. Itching. Lacrimation. Blurred vision.
Symptoms/effects after ingestion	: Not expected to present a significant hazard under anticipated conditions of normal use.
Other information	: No experimental study on the product is available. The information given is based on our knowledge of the components and the classification of the product is determined by calculation.

SECTION 12 Ecological information

12.1. Ecotoxicity

Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

2-methylisothiazol-3(2H)-one (2682-20-4)	
LC50 - Fish [1]	6 mg/l (96 h, Oncorhynchus mykiss, OECD 203)
EC50 - Crustacea [1]	1.68 mg/l (48 h, Daphnia sp., OECD 202)
EC50 - Other aquatic organisms [1]	34.6 mg/l (3 h, DIN 38412-3)
EC50 72h - Algae [1]	0.157 mg/l (72 h, Pseudokirchneriella subcapitata, OECD 201)
NOEC chronic fish	2.1 mg/l (28 d, Pimephales promelas, OECD 210)
NOEC chronic crustacea	0.55 mg/l (21 d, Daphnia sp., OECD 211)
NOEC chronic algae	0.03 mg/l (72 h, Pseudokirchneriella subcapitata, OECD 201)

12.2. Persistence and degradability

Fix-a-Flat	
Persistence and degradability	Biodegradability in water: no data available.

12.3. Bioaccumulative potential

Fix-a-Flat	
Bioaccumulative potential	No bioaccumulation data available.

2-methylisothiazol-3(2H)-one (2682-20-4)	
BCF - Fish [1]	3.16
Partition coefficient n-octanol/water (Log Kow)	≤ 0.32 (OECD 117)

Fix-a-Flat

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

12.4. Mobility in soil

Fix-a-Flat

Ecology - soil

Because of its high volatility, the product is unlikely to cause ground or water pollution.

12.5. Other adverse effects

Ozone : Not classified
Effect on global warming : No known effects from this product.
Fluorinated greenhouse gases : No

SECTION 13 Disposal considerations

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations : Container under pressure. Do not drill or burn even after use. Dispose in a safe manner in accordance with local/national regulations.
Ecological waste information : Avoid release to the environment.

SECTION 14 Transport information

In accordance with DOT / TDG / IMDG / IATA

14.1. UN number


UN-No. (DOT) : UN1950
UN-No. (TDG) : UN1950
UN-No. (IMDG) : 1950
UN-No. (IATA) : 1950

14.2. UN Proper Shipping Name

Proper Shipping Name (DOT) : Aerosols
Proper Shipping Name (TDG) : AEROSOLS
Proper Shipping Name (IMDG) : AEROSOLS
Proper Shipping Name (IATA) : Aerosols, non-flammable

14.3. Transport hazard class(es)

DOT
Transport hazard class(es) (DOT) : LTD QTY (LTD QTY Y)
Hazard labels (DOT) : LTD QTY, LTD QTY Y



TDG
Transport hazard class(es) (TDG) : 2.2

IMDG
Transport hazard class(es) (IMDG) : 2.2

IATA
Transport hazard class(es) (IATA) : 2.2

14.4. Packing group

Packing group (DOT) : Not applicable

Fix-a-Flat

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Packing group (TDG) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

Special transport precautions : Limited quantity for packages less than 30 kg gross and inner packagings less than 1 L

DOT
UN-No. (DOT) : UN1950
DOT Packaging Exceptions (49 CFR 173.xxx) : 306
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg
DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other : 25 - Protected from sources of heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

TDG
UN-No. (TDG) : UN1950
TDG Special Provisions : 80 - Despite section 1.17 of Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases), a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with the requirements for transporting gases in Part 5 (Means of Containment), 107 - (1) These Regulations, except for Parts 1 and 2, do not apply to the offering for transport, handling or transport of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a vessel on a domestic voyage, if the aerosols or gas cartridges have a capacity less than or equal to 50 mL.
(2) Subsection (1) does not apply to self-defence spray.
Explosive Limit and Limited Quantity Index : 1 L
Excepted quantities (TDG) : E0
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index : 75 L
Emergency Response Guide (ERG) Number : 126

IMDG
Special provision (IMDG) : 63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG) : SP277
Excepted quantities (IMDG) : E0
Packing instructions (IMDG) : P207, LP200
Packing provisions (IMDG) : PP87, L2
EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG) : None
Stowage and handling (IMDG) : SW1, SW22
Segregation (IMDG) : SG69

IATA
Special provision (IATA) : A98, A145, A167, A802

Fix-a-Flat

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
ERG code (IATA)	: 2L

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Contains chemical(s) subject to TSCA 12b export notification if product is shipped outside the U.S

2-methylisothiazol-3(2H)-one	CAS-No. 2682-20-4	0.0015 - 0.01%
------------------------------	-------------------	----------------

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Propan-2-ol	CAS-No. 67-63-0	< 0.1%
-------------	-----------------	--------

15.2. International regulations

CANADA

Glycerol (56-81-5)

Listed on the Canadian DSL (Domestic Substances List)

Cellulose (9004-34-6)

Listed on the Canadian DSL (Domestic Substances List)

Quartz (SiO₂) (14808-60-7)

Listed on the Canadian DSL (Domestic Substances List)

Magnesium oxide (1309-48-4)

Listed on the Canadian DSL (Domestic Substances List)

Propan-2-ol (67-63-0)

Listed on the Canadian DSL (Domestic Substances List)

2-methylisothiazol-3(2H)-one (2682-20-4)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

Fix-a-Flat

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

National regulations

Glycerol (56-81-5)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Cellulose (9004-34-6)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Quartz (SiO₂) (14808-60-7)

Listed on IARC (International Agency for Research on Cancer)
Listed as carcinogen on NTP (National Toxicology Program)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Magnesium oxide (1309-48-4)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Propan-2-ol (67-63-0)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

2-methylisothiazol-3(2H)-one (2682-20-4)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16 Other information

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Revision date : 3/10/2025
Issue date : 3/24/2023
Data sources : Supplier's safety documents.
Training advice : Training staff on good practice.

Full text of hazard classes and H-statements

H225	Highly flammable liquid and vapor
H229	Pressurized container; may burst if heated
H301	Toxic if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H330	Fatal if inhaled
H336	May cause drowsiness or dizziness

Fix-a-Flat

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Full text of hazard classes and H-statements	
H350	May cause cancer.
H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

Indication of changes:
Sections 1-16.

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.